

ATF40A-D

DC Tubeaxial fan:
40 × 40 × 20(mm)



► **Contacts parameters**

SPECIFICATION												
S:Sleeve Bearing H:Hydraulic Bearing B:Two ball bearing												
Model	Define	Bearing			Voltage (VDC)	Current (A)	Power (W)	Speed (RPM)	AirFlow (CFM)	Pressure (mm-H2O)	Noise (dBA)	Weight (g)
		S	H	B								
ATF40A-D5H	H	*		*	5	0.25	1.25	6000	6.69	5.88	32.4	23
ATF40A-D5M	M	*		*	5	0.20	1.00	5000	5.59	4.56	28.2	23
ATF40A-D5L	L	*		*	5	0.15	0.75	4000	4.23	3.25	25.6	23
ATF40A-D12H	H	*		*	12	0.25	3.00	7000	7.8	5.88	32.4	23
ATF40A-D12M	M	*		*	12	0.20	2.40	6000	6.69	4.56	28.2	23
ATF40A-D12L	L	*		*	12	0.15	1.80	5000	5.59	3.25	25.6	23
ATF40A-D24H	H	*		*	24	0.15	3.60	7000	7.8	5.88	32.4	23
ATF40A-D24M	M	*		*	24	0.12	2.88	6000	6.69	4.56	28.2	23
ATF40A-D24	L	*		*	24	0.08	1.12	5000	5.59	3.25	25.6	23

► **OUTLINE DIMENSION WITH INSTALLATION SIZE** Unit: mm



